





CTL SystemWare


## Power Line Antenna (PLA)

### Features

- Portable and Lightweight
- 1 kHz - 50 MHz Frequency Coverage
- >10 Hour Battery Life
- Up to 64 dB of Attenuation
- Automated Switching Between States of Power via USB Control
- Manual Switching for use with External Receiver or Spectrum Analyzer

### Specifications

- Line Input: 0-264 VAC, 50/60 Hz
- Input Connector: AC Line In
- Output Connector: Two BNC Ports, 50 Ohm
- Bandwidth: 1 kHz to 50 MHz
- Gain: 18dB @ 0 Attenuation Setting
- Noise Voltage: 23 dB nom.
- Power Supply Voltage: 12VDC
- Power Consumption: <4W
- Filtering: High-Pass and Notch Filters Attenuate the AC Line Components More than 140 dB
- Attenuation (software): 64 dB Attenuator, 1dB Steps
- Attenuation (manual): 0,10,20,40 dB Attenuator or Combination of Two Buttons
- Manual Control: 3 Channels PN,PG,NG
- USB Software Control: 3 Channels PN,PG, NG
- Physical Size: 6"x6.25"x1.5"



CTL SystemWare

Turnkey **Products**

Comprehensive **Training**

Customized **Services**

CTL-SystemWare provides world class technical security solutions for the protection of government, corporate and private interests. Our services and solutions are uniquely designed to help our clients improve communications, protect intellectual property, secure the integrity of information systems and networks, and increase efficiency and mission effectiveness. CTL-SystemWare provides individualized risk mitigation solutions for modern technical problems.